

```
# tästä tulee ./themes/src/main/resources-community/theme/base/admin/messages/messages_fi.properties
# ks. muut kieliversiot tästä:
# https://github.com/keycloak/keycloak/tree/master/themes/src/main/resources-
community/theme/base/admin/messages
# Korvaa englanninkielinen viesti =:n jälkeen suomenkielisellä
#
# malli:
# Alkuperäinen rivi:
# doSave=Save
# korvataan rivillä:
# doSave=Tallenna
```

```
invalidPasswordMinLengthMessage=Invalid password: minimum length {0}.
invalidPasswordMinLowerCaseCharsMessage=Invalid password: must contain at least {0} lower case
characters.
invalidPasswordMinDigitsMessage=Invalid password: must contain at least {0} numerical digits.
invalidPasswordMinUpperCaseCharsMessage=Invalid password: must contain at least {0} upper case
characters.
invalidPasswordMinSpecialCharsMessage=Invalid password: must contain at least {0} special characters.
invalidPasswordNotUsernameMessage=Invalid password: must not be equal to the username.
invalidPasswordRegexPatternMessage=Invalid password: fails to match regex pattern(s).
invalidPasswordHistoryMessage=Invalid password: must not be equal to any of last {0} passwords.
invalidPasswordBlacklistedMessage=Invalid password: password is blacklisted.
invalidPasswordGenericMessage=Invalid password: new password does not match password policies.
```

```
ldapErrorInvalidCustomFilter=Custom configured LDAP filter does not start with "(" or does not end with
)".
ldapErrorConnectionTimeoutNotNumber=Connection Timeout must be a number
ldapErrorReadTimeoutNotNumber=Read Timeout must be a number
ldapErrorMissingClientId=Client ID needs to be provided in config when Realm Roles Mapping is not used.
ldapErrorCantPreserveGroupInheritanceWithUIDMembershipType=Not possible to preserve group
inheritance and use UID membership type together.
ldapErrorCantWriteOnlyForReadOnlyLdap=Can not set write only when LDAP provider mode is not
WRITABLE
ldapErrorCantWriteOnlyAndReadOnly=Can not set write-only and read-only together
ldapErrorCantEnableStartTlsAndConnectionPooling=Can not enable both StartTLS and connection pooling.
```

```
clientRedirectURIsFragmentError=Redirect URIs must not contain an URI fragment
clientRootURLFragmentError=Root URL must not contain an URL fragment
```

```
pairwiseMalformedClientRedirectURI=Client contained an invalid redirect URI.
pairwiseClientRedirectURIsMissingHost=Client redirect URIs must contain a valid host component.
pairwiseClientRedirectURIsMultipleHosts=Without a configured Sector Identifier URI, client redirect URIs
must not contain multiple host components.
pairwiseMalformedSectorIdentifierURI=Malformed Sector Identifier URI.
pairwiseFailedToGetRedirectURIs=Failed to get redirect URIs from the Sector Identifier URI.
pairwiseRedirectURIsMismatch=Client redirect URIs does not match redirect URIs fetched from the Sector
Identifier URI.
```